



Specifications Ledvance LED Panel Eco  
36W 3240lm 865 Daylight | 60x60cm -  
UGR <19

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 243687                                 |
| EAN                      | 4058075386723                          |
| Brand                    | Ledvance                               |
| Manufacturer Name        | ECO PANEL600 36W 865 UGR19 WT FS1 LEDV |
| Any Lamp all-in warranty | 3 Years                                |
| Average Lifetime (h)     | 50000                                  |
| Series                   | Panel Led                              |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 865 Daylight      |
| Colour temperature (Kelvin) | 6500 Daylight     |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Luminous Efficacy (lm/W)    | 90                |
| IP-rating                   | IP40              |
| Impact Protection (IK)      | IK02 - 0.20 joule |

|                    |                              |
|--------------------|------------------------------|
| Fixture Connection | Push button terminal, 2-pole |
|--------------------|------------------------------|

|              |       |
|--------------|-------|
| Power factor | >0.95 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                                |
|----------------------|--------------------------------|
| Unified Glare Rating | < 19 - for offices and schools |
|----------------------|--------------------------------|

|               |                  |
|---------------|------------------|
| Optical Cover | PS (Polystyrene) |
|---------------|------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | +10 to +45 |
|-----------------------|------------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |           |
|---------|-----------|
| Housing | Aluminium |
|---------|-----------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
|----------------|---------|

|             |     |
|-------------|-----|
| Length (mm) | 600 |
|-------------|-----|

|            |     |
|------------|-----|
| Width (mm) | 600 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 34 |
|-------------|----|

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process