



Specifications Philips CoreLine LED Downlight DN135B 4000K 1000lm LED10S PSU II WH



[View Product](#)

General Information

| | |
|--------------------------|-----------------------------|
| SKU | 222765 |
| EAN | 8718696070437 |
| Brand | Philips |
| Manufacturer Name | DN135B LED10S/840 PSU II WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 135 |

| | |
|--------------------------|------------------------------------|
| Luminous Efficacy (lm/W) | 76.9 |
| Power factor | >0.90 |
| Installation Depth (mm) | 30 |
| Unified Glare Rating | < 25 - for hallways and staircases |
| Optical Cover | Opal |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|-----------------------|---|
| EOC8 | 7043799 |
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP20 |
| Operating Temperature | 0 to +35 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PIP [Push-in connector and pull relief] |
| Series | DN135B |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 30 |
| Diameter (mm) | 165 |

Why Any-lamp?

Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation
Type of sensor **No Sensor**

 **Up to 7 years warranty**  **Easy return process**